

# TECHNICAL DATA SHEET

## POLYETHYLENE BRALEN+ FA 03-01

### LDPE for film

TIPELIN / TIPOLEN / TIPPLEN / TATREN / BRALEN+

The joint product portfolio of MOL Petrochemicals and Slovnaft provides infinite opportunities

### DESCRIPTION

**BRALEN+ FA 03-01** is a film grade of low density polyethylene with good processability, flexibility, toughness and good tear strength. This grade is additives free.

### APPLICATIONS

**BRALEN+ FA 03-01** is designed for production of heavy duty and shrink films of thickness 0.07 to 0.22 mm. It is well suited for blow moulding of various containers, bottles, pipes, sheets and profiles extrusion and for injection moulding.

### PROPERTIES

	Test method	Unit	Typical value
MFR (190 °C/2.16 kg)	ISO 1133-1	g/10 min	0.25
Density (23°C)	ISO 1183-1	kg/m <sup>3</sup>	920
Tensile strength (MD/TD) *	ISO 527-1,3	MPa	27/25
Tensile strain at break (MD/TD) *	ISO 527-1,3	%	200/500
Dart drop *	ISO 7765-1 method A	g	280
Haze *	ASTM D 1003	%	15
Vicat softening temperature	ISO 306/A 50	°C	93

Typical properties, not to be used as specification.

\*Film properties tested using 50 µm thick blown film extruded at melt temperature of 180°C and a blow up ratio 2.5:1.

### PROCESSING

**BRALEN+ FA 03-01** can be used in conventional extrusion machines. Recommended processing temperatures are 170-220 °C.

# TECHNICAL DATA SHEET

## POLYETHYLENE BRALEN+ FA 03-01

### LDPE for film

TIPELIN / TIPOLEN / TIPPLEN / TATREN / BRALEN+

The joint product portfolio of MOL Petrochemicals and Slovnaft provides infinite opportunities

2

### STORAGE AND HANDLING

Pellets are packed in 25 kg PE-LD bags and transported on stretch wrapped pallets at eligible load of polymer 1375 kg. Heat treated pallets are available as well. We use adhesive between the bags in order to avoid their slipping. Pay attention to this fact during the removing of the bags from the pallets. The preferred method is to lift the bag at first without rotation. Transportation in a road silo or rail silo is also available. For more detailed information please contact SLOVNAFT and MOL Petrochemicals sales representative.

Since polyethylene is a combustible substance, the fire safety rules applicable for combustible materials in warehouses and store rooms should be observed.

If polymer is stored in conditions of high humidity and fluctuating temperatures, then atmospheric moisture can condense inside the packing. If it happened, it is recommended the pellets to be dried before use. During the storage polyethylene should not be exposed to UV radiation and temperatures above 40°C. Producer does not take responsibility for any damages caused by adverse storage.

### REACH STATEMENT

Polymers are exempt of REACH registration. However, their raw materials which mean monomers and relevant additives have been registered. SLOVNAFT, a.s. is committed to fully respect legislation and will only use REACH compliant raw materials. At this point in time LDPE BRALEN+ does not contain any substances specifically identified as SVHC at levels greater than 0.1%.

### SAFETY

See MSDS.

### RECYCLING

Polyethylene resins are suitable for recycling using modern recycling methods. In-house production waste should be kept clean to facilitate direct recycling.

### DISCLAIMER

The information provided in this publication has been compiled to the best of our present knowledge. However, in view of the various applications of polyethylene resins and the equipment used, the processing conditions may differ.

The recommendations and data herein are to be construed as informational only and do not relieve users from carrying out their own tests and experiments prior to processing in order to check suitability for a specific use. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed. Our products are under continuous development, therefore we reserve the right to change the information presented in this brochure at our own discretion.

The REACH statement herein does not constitute legal advice. The REACH statement is provided for informational purpose only.

# TECHNICAL DATA SHEET

## POLYETHYLENE BRALEN+ FA 03-01

### LDPE for film

TIPELIN / TIPOLEN / TIPPLEN / TATREN / BRALEN+

The joint product portfolio of MOL Petrochemicals and Slovnaft provides infinite opportunities

#### MANUFACTURER

##### SLOVNAFT, a.s.

Address: Vlčie hrdlo 1  
824 12 Bratislava  
Slovak Republic  
Internet: [www.slovnaft.sk](http://www.slovnaft.sk)  
E-mail: [infopolymer@slovnaft.sk](mailto:infopolymer@slovnaft.sk)

#### TECHNICAL SERVICE

##### SLOVNAFT, a.s.

Address: Vlčie hrdlo 1  
824 12 Bratislava  
Slovak Republic  
Telephone: + 421 2 5859 7250  
+ 421 2 5859 7257  
E-mail: [polymerservice@slovnaft.sk](mailto:polymerservice@slovnaft.sk)

#### SALES ORGANIZATION

##### SLOVNAFT, a.s.

Address: Vlčie hrdlo 1  
824 12 Bratislava  
Slovak Republic  
Telephone: +421 2 5859 7515  
+421 2 5859 7622  
+421 2 5859 7741  
+421 2 5859 7231  
E-mail: [polymersales@slovnaft.sk](mailto:polymersales@slovnaft.sk)

##### MOL Plc.

##### Domestic Polymer Sales MOL

Address: H-3581 Tiszaújváros  
P.O. Box: 20  
Hungary  
Telephone: +36 49 521 355  
Fax: +36 49 886 491  
E-mail: [polymersales@mol.hu](mailto:polymersales@mol.hu)

##### MOL Germany GmbH.

Address: Im Trutz Frankfurt 49  
D-60322 Frankfurt am Main  
Germany  
Telephone: +49 69 154 04 0  
Fax: +49 69 154 04 41  
E-mail: [polymersales@molgermany.de](mailto:polymersales@molgermany.de)

##### MOL- Austria Handels GmbH.

Address: Walcherstrasse 11A  
7. Stock  
A-1020 Wien  
Austria  
Telephone: +43 1 211 20 1120  
Fax: +43 1 211 20 1198  
E-mail: [JHauk@molaustria.at](mailto:JHauk@molaustria.at)

# TECHNICAL DATA SHEET

## POLYETHYLENE BRALEN+ FA 03-01

### LDPE for film

TIPELIN / TIPOLEN / TIPPLEN / TATREN / BRALEN+

The joint product portfolio of MOL Petrochemicals and Slovnaft provides infinite opportunities

4

#### TVK Italia S.r.l.

Address: Via Teulié, 1  
20136 Milano  
Italy  
Telephone: +39 02 58 30 5523  
Fax: +39 02 58 30 3492  
E-mail: [tvkitaly@it.tvk.eu](mailto:tvkitaly@it.tvk.eu)

#### French Liaison Representative

Address: Paris  
France  
Telephone: +33 1 64 32 44 17  
Mobile Phone: +33 7 89 86 10 64  
E-mail: [husson.iren@fr.tvk.eu](mailto:husson.iren@fr.tvk.eu)

#### MOL Ukraine LLC.

Address: 04655 Kiev  
Moskovskiy ave. 23  
7th floor  
Ukraine  
Telephone: +380 44 374 00 80  
Fax: +380 44 374 00 90  
E-mail: [JZavojko@mol-ukraine.com.ua](mailto:JZavojko@mol-ukraine.com.ua)

#### SLOVNAFT Polska S.A.

PetChem Department  
Address: ul. Postępu 17D  
02-676 Warszawa  
Poland  
Telephone: +48 22 545 70 70  
Fax: +48 22 545 70 60  
E-mail: [petchem@slovnaft.pl](mailto:petchem@slovnaft.pl)

#### TIFON d.o.o.

Address: Savska cesta 41/XIII  
HR – 10000 Zagreb  
Croatia  
Telephone: +385 1 6160 600  
Fax: +385 1 6160 601  
E-mail: [polymersales@tifon.hr](mailto:polymersales@tifon.hr)

#### SC. MOL Romania P.P. SRL

Address: Str. Danielopolu 4-6  
ET2 Sector 1 Cod 014 134  
Bucuresti  
Romania  
Telephone: +40 21 204 85 00  
Fax: +40 21 232 10 59  
E-mail: [petchem@molromania.ro](mailto:petchem@molromania.ro)

#### Other European Countries

Telephone: +36 49 521 355  
+36 70 458 4563  
+36 70 373 9209  
Fax: +36 49 886 491  
E-mail: [polymersales@mol.hu](mailto:polymersales@mol.hu)

January 2016